

Welly S3 - T13 AAM - Revo Stage 1 - Boost 9, Timing 9 + 2.25deg.

Friday 14 May 2010 19:56:33  
 8L0 906 018 N 1.8L R4/5VT G 0002

Group A: '002				
	RPM	Load	Inj. On Time	Mass Flow
TIME				
STAMP	/min	%	ms	g/s
20.78	1600	47.4	4.1	14.61
22	2520	84.2	6.56	41.94
23.29	4640	191.7	21.32	193.83
24.5	7040	136.1	10.66	173.03
25.79	5600	191.7	20.09	207.58
27	6760	161.7	16.81	208.58
28.28	4920	191.7	20.09	193.83
29.48	5560	191.7	20.09	209
30.68	6120	180.5	18.45	209.14
31.99	6600	162.4	16.81	202.44
33.2	6960	163.9	16.81	202.78
34.38	5480	191.7	20.5	205.72
35.58	5760	191	19.68	214
36.78	6080	182	18.86	206
37.98	6320	172.9	17.63	206.44
39.4	6520	165.4	17.22	204.58
40.68	6680	166.2	17.22	204.56
41.98	6800	163.9	17.22	203.69
43.29	6960	26.3	2.46	0
44.49	5600	176.7	18.04	205.31
45.67	5720	179.7	18.45	210
46.87	4760	6	1.23	0
48.07	4440	5.3	0	5.25

Group B: '118					
	RPM	Temperature	Load	Absolute Pres.	
TIME					
STAMP	/min	°C	%	mbar	
19.79	1240		27	0	1030
21.18	1840		26	0	1040
22.4	3000		24	0	1250
23.69	5680		21	77.6	2210
24.99	4560		16	71.4	1500
26.19	6000		18	73.7	2190
27.48	7080		18	0	2040
28.68	5160		20	74.5	2230
29.88	5760		20	74.1	2240
31.19	6320		21	68.2	2100
32.39	6760		21	64.3	2010
33.59	6720		21	56.1	1620
34.78	5600		23	75.3	2240
35.99	5880		23	72.9	2220
37.19	6120		24	69.8	2140
38.49	6360		24	67.8	2090
39.88	6560		24	67.1	2040
41.08	6720		24	65.9	2030
42.39	6880		25	65.1	2000
43.69	5440		23	68.2	1360
44.89	5640		26	76.1	2280
46.07	5760		26	73.3	2250
47.27	4640		24	0	1130

49.38	3960	8.3	0	6.72	48.47	4320	24	0	1060
50.68	3600	9.8	0	8.19	49.86	3840	26	0	1050
51.96	3240	9.8	0	5.83	51.17	3480	27	0	1050
53.16	2920	11.3	0	6.17	52.36	3160	27	0	1040
54.36	2680	10.5	0	5.5	53.56	2840	27	0	1040
55.56	2440	10.5	0	4.69	54.76	2640	27	0	1040
56.97	2200	10.5	0	4.86	55.96	2400	27	0	1030
58.17	2040	11.3	0	4.81	57.37	2120	28	0	1030
59.37	1440	11.3	1.64	3.14	58.57	2000	28	0	1030
60.66	1320	10.5	1.23	2.81	59.86	2120	28	0	1020
62.07	3040	14.3	1.64	9.17	61.16	2520	28	0	1020
63.27	3120	109.8	9.02	72.25	62.47	3040	28	0	1020
64.47	3560	182	17.22	134.72	63.67	3200	26	7.5	1370
65.76	4400	191.7	20.91	172.92	64.96	3840	24	71.4	2260
66.96	5160	191.7	20.5	197.08	66.16	4680	21	72.9	2380
68.28	5800	191.7	20.09	213.11	67.48	5440	21	76.1	2290
69.46	6360	171.4	17.63	214.86	68.69	6000	21	72.9	2210
70.66	6800	170.7	17.22	202.86	69.86	6520	23	67.5	2070
71.86	6680	9	1.23	0	71.06	6880	23	64.3	2000
73.06	5480	178.9	18.45	207.25	72.26	5360	21	76.1	1280
74.37	4840	6.8	1.23	0	73.46	5600	24	77.3	2270
75.57	4040	5.3	0	4.53	74.77	4400	23	0	1150
76.95	3480	8.3	0	5	75.97	3560	24	0	1060
78.15	3360	9	0	6.25	77.35	3400	24	0	1050
79.46	3240	10.5	0	7	78.55	3320	26	0	1040
80.95	3120	11.3	0	6.58	79.95	3200	27	0	1040
82.16	3040	11.3	0	6.75	81.35	3080	27	0	1040